

Overview

Cellapps M2M is the product which would monitor and control your remote units/ equipments & also sends you SMS in case of alarm conditions in the most effective and economic way. Cellapps M2M is an advanced yet simplified Remote Terminal Unit. Taking advantage of the reliable, widespread GSM networks. Cellapps M2M becomes a remotely accessible unit from any part of the world. Alarm conditions can be configured for monitoring temperature. Since Cellapps M2M supports SMS protocols, the device can be configured to send SMS, the device can be configured to send alert SMS whenever alarm conditions occur.



APPLICATION AREAS:-

- ∠ Security Systems
- ∠ Building Surveillance & Control
- ∠ Heating, Lighting & Climate Control
- Remote monitoring and Equipment Control

FEATURES:-

- ∠ Local and Remote Configuration
- ∠ Real Time Clock(RTC)
- Facility to configure security option to allow control only through pre defined mobile numbers.
- Provision for configuring five mobile numbers, can be customized.
- Multiple user messages for fault.
- Can be custom designed for OEM products.

SPECIFICATIONS:-

Module: 850/900/1800 MHz Quad Band GSM/GPRS module

System: GSM

SIM: External SIM 1.8V & 3V

SMS: Supports Text

LED indication: Relay Output, Power, GSM

Connectors/Switches: RS-232 Serial, SIM card Holder, SMA antenna connector for GSM

Power Supply: Wide DC Input Voltage Range (12 to 24V DC, 3A)

Relative Humidity: 10%-90% RH

Dimension: $150 \text{mm}(L) \times 95 \text{mm}(W) \times 60 \text{mm}(H)$

Antenna: GSM Antenna

Enclosure: ABS

Operational -10° C to 60° C

temperature range:

Developed By:

11, Premium House, Gandhigram Rly Station, Navrangpura, Ahmedabad - 380 009 Phone: 91-79-26580392,26574356 Web: www.saltriver.com